



Product Service

CERTIFICATE

No. Z2 099333 0055 Rev. 03

Model(s):

LR6-72HV-xxxM, (xxx=320 to 350 in step of 5)
 LR6-60HV-xxxM, (xxx=270 to 300 in step of 5)
 LR6-72PH-xxxM, (xxx=340 to 385 in step of 5)
 LR6-60PH-xxxM, (xxx=280 to 320 in step of 5)
 LR6-72HPH-xxxM, (xxx=350 to 405 in step of 5)
 LR6-72HIH-xxxM, (xxx=350 to 405 in step of 5)
 LR6-60HPH-xxxM, (xxx=295 to 335 in step of 5)
 LR6-60HIH-xxxM, (xxx=295 to 335 in step of 5)
 LR6-72OPH-xxxM, (xxx=385 to 400 in step of 5)
 LR6-60OPH-xxxM, (xxx=335 to 350 in step of 5)
 LR6-72HPH-xxxMC, (xxx=375 to 390 in step of 5)
 LR6-60HPH-xxxMC, (xxx=305 to 325 in step of 5)
 LR4-72HPH-xxxM, (xxx=400 to 460 in step of 5)
 LR4-72HIH-xxxM, (xxx=400 to 460 in step of 5)
 LR4-60HPH-xxxM, (xxx=330 to 380 in step of 5)
 LR4-60HIH-xxxM, (xxx=330 to 380 in step of 5)
 LR4-72ZPH-xxxM, (xxx=420 to 435 in step of 5)
 LR4-60ZPH-xxxM, (xxx=350 to 365 in step of 5)
 LR6-60ZPH-xxxM, (xxx=330 to 355 in step of 5)
 xxx is standing for rated output power at STC

Parameters:

Severity of	
Salt Mist Test:	Severity 6 and severity 1
Application Class:	Class A
Maximum System Voltage:	1500 V DC
Fire Safety Class:	Class C
Construction:	Framed, with Junction box, cable and connector.

Tested according to:

IEC 61215:2005
 IEC 61730-1:2004
 IEC 61730-1:2004/AMD1:2011
 IEC 61730-1:2004/AMD2:2013
 IEC 61730-2:2004
 IEC 61730-2:2004/AMD1:2011
 IEC 61701:2011

Production Facility(ies):

096558, 002875, 001192, 090968, 099626, 099605, 099606, 097323, 102892, 103410, 103841

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

A4 / 07.17